



Light extension rod




Thread	Hex		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[ft/in]		
T38 - T38	32	1 1/4"	3050	10'	18.4	EH32M38-3050
			3660	12'	22.1	EH32M38-3660

Round extension rod




Thread	Outside diameter		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[ft/in]		
T38 - T38	38	1 1/2"	3050	10'	24.7	ER38M38-3050
			3660	12'	29.4	ER38M38-3660
			4270	14'	34.7	ER38M38-4270
			4880	16'	39.7	ER38M38-4880
			5490	18'	44.6	ER38M38-5490

Male / Female rod




Thread	Outside diameter		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[ft/in]		
T38 - T38	38	1 1/2"	900	3'	8.0	ER38M38MF-900
			1220	4'	9.7	ER38M38MF-1220
			1525	5'	13.3	ER38M38MF-1525
			1830	6'	16.0	ER38M38MF-1830
			2440	8'	21.3	ER38M38MF-2440
			3050	10'	25.9	ER38M38MF-3050
			3660	12'	30.7	ER38M38MF-3660

Tandem rod




Thread	Outside diameter		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[ft/in]		
T38 - T38	38	1 1/2"	3050	10'	24.4	ER38M38T-3050
			3660	12'	29.3	ER38M38T-3660

Coupling sleeve



Thread	Outside diameter(D)		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[in]		
T38 - T38	54	2 1/8"	190	7 1/2"	2.0	CM38

Crossover coupling



Thread	Outside diameter(D)		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[in]		
T38 - R32	54	2 1/8"	188	7 1/2"	2.2	CM38R32
T38 - T45	63	2 1/2"	215	8 1/2"	3.4	CM45M38