



Hex Drifting rod



Thread	Hex		Length(L)		Weight [Kg]	Part number		
	[mm]	[in]	[mm]	[ft/in]				
R32 - R38	32	1 1/4"	3100	10' 2"	19.7	EH32R38R32-3100		
			3700	12' 2"	23.3	EH32R38R32-3700		
			4310	14' 2"	27.0	EH32R38R32-4310		
			4920	16' 2"	30.9	EH32R38R32-4920		
R32 - R38	35	1 3/8"	3100	10' 2"	23.9	EH35R38R32-3100		
			3700	12' 2"	28.5	EH35R38R32-3700		
			4310	14' 2"	33.2	EH35R38R32-4310		
			4920	16' 2"	36.7	EH35R38R32-4920		
R32 - T38	35	1 3/8"	5530	18' 2"	41.3	EH35R38R32-5530		
			32	1 1/4"	3100	10' 2"	19.7	EH32M38R32-3100
					3700	12' 2"	23.3	EH32M38R32-3700
					4310	14' 2"	27.0	EH32M38R32-4310
4920	16' 2"	30.9			EH32M38R32-4920			
R32 - T38	35	1 3/8"	3100	10' 2"	23.9	EH35M38R32-3100		
			3700	12' 2"	28.5	EH35M38R32-3700		
			4310	14' 2"	33.2	EH35M38R32-4310		
			4920	16' 2"	36.7	EH35M38R32-4920		
			5530	18' 2"	41.3	EH35M38R32-5530		

Round Drifting rod




Thread	Outside diameter		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[ft/in]		
R32 - R32	32	1 1/4"	1830	6'	8.0	ER32R32-1830
			2440	8'	11.5	ER32R32-2440
			3050	10'	16.2	ER32R32-3050
			3660	12'	19.5	ER32R32-3660

Male / Female Drifting rod




Thread	Outside diameter		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[ft/in]		
R32 - R32	32	1 1/4"	1830	6'	9.4	ER32R32MF-1830
			2440	8'	12.9	ER32R32MF-2440
			3050	10'	17.4	ER32R32MF-3050
			3660	12'	20.6	ER32R32MF-3660

Coupling sleeve



Thread	Outside diameter(D)		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[in]		
R32 - R32	45	1 3/4"	150	6"	1.0	CR32D
R38 - R38	54	2 1/8"	170	6 3/4"	1.7	CR38D

Crossover coupling



Thread	Outside diameter(D)		Length(L)		Weight [Kg]	Part number
	[mm]	[in]	[mm]	[in]		
R32 - R25	45	1 3/4"	175	6 7/8"	1.5	CR32R25
R32 - R28	45	1 3/4"	171	6 3/4"	1.4	CR32R28
R32 - R38	54	2 1/8"	181	7 1/8"	2.1	CR38R32
R32 - T38	54	2 1/8"	188	7 1/2"	2.2	CM38R32