



www.tabe-hammers.com



MARTILLOS
HIDRÁULICOS

HYDRAULIC
BREAKERS

BRISE ROCHES
HYDRAULIQUES

MARTILLOS HIDRÁULICOS
HYDRAULIC BREAKERS
BRISE ROCHES HYDRAULIQUES



Sistema Pare
Pare System
Non-contact strike system



Circuito engrase automático
Automatic lubrication
Graissage aut.



Trabajos submarinos
Under-water excavation
Travaux sous-l'eau



Cambio de frecuencia
Stroke switching
Changement de vitesse



Protección latiguillos
Hose-protection
Protection de flexibles

S - serie
O - option

	kg	t.	mm	l/min.	Bar	min.	D(mm)	L(mm)	kg						β system
AGB-95	105	0,8-3,5	1046	20-35	80-100	650-1200	45	420	7,8	-	-	-	-	-	-
AGB-175	170	2,5-4,5	1060	40-50	80-90	1000-1200	50	450	6	O	-	O	-	-	-
AGB-275	275	3,5-5,5	1220	60-70	80-90	850-1000	65	610	15	S	-	O	-	-	-
AGB-375	340	4,5-7	1300	65-75	130-135	800-950	65	610	15	S	-	O	-	-	-
AGB-475BC	410	6-10	1338	70-80	140-150	850-975	84	700	26	S	-	O	-	-	-
AGB-575	600	8-15	1650	90-125	130-140	700-1000	90	850	39	S	-	-	-	-	-
AGB-10B	950	10-16	1870	85-110	150-175	450-590	105	1000	61	S	S	S	O	S	-
AGB-12	1300	15-23	2100	90-120	150-170	450-700	120	1100	90	O	S	O	O	S	-
AGB-15	1470	19-25	2265	120-145	150-180	400-800	135	1100	112	S	S	S	S	S	-
AGB-18	1950	24-28	2390	130-155	160-190	450-750	135	1100	112	S	S	S	S	S	O
AGB-20STA	2300	25-35	2485	175-220	160-190	350-600	150	1320	166	S	S	S	S	S	O
AGB-30STA	3300	30-50	2815	205-245	160-190	300-550	165	1525	205	S	S	S	S	S	O
AGB-40	4850	45-70	3025	250-340	160-190	250-340	210	1600	275	S	S	S	S	S	O

El fabricante se reserva el derecho de cambiar estas características técnicas sin previo aviso.
Manufacturer has the right to change these technical features without previous notice.
Le fabricant se réserve le droit de modifier les données techniques sans preavuu.

TALLERES BETOÑO S.A.

Beclarra 8 • 01010 VITORIA-SPAIN • tel. 00 34 902 247 250 • fax. 00 34 945 224 177
tabe@tabe-hammers.com



www.tabe-hammers.com